

MIAMI-DADE COUNTY PRODUCT CONTROL SECTION

11805 SW 26 Street, Room 208 T (786) 315-2590 F (786) 315-2599

www.miamidade.gov/economy

DEPARTMENT OF REGULATORY AND ECONOMIC RESOURCES (RER) BOARD AND CODE ADMINISTRATION DIVISION

NOTICE OF ACCEPTANCE (NOA)

HWD Acquisition, Inc. dba Hurd Windows & Doors 575 South Whelen Avenue Medford, WI 54451

Scope:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County RER - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. RER reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code, including the High Velocity Hurricane Zone.

DESCRIPTION: Series "Feel Safe" Aluminum Clad Wood Fixed Window - L.M.I.

APPROVAL DOCUMENT: Drawing No. 1404, titled "Feel Safe Aluminum Clad Wood Impact Fixed Casement Window, sheets 1 through 6 of 6, dated 07/21/05, with revision E1 dated 12/18/14, prepared by W. W. Schaefer Engineering & Consulting, P.A., signed and sealed by Warren W. Schaefer, P.E., bearing the Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Section

MISSILE IMPACT RATING: Large and Small Missile Impact Resistant

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state, model/series, and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA revises NOA# 11-1006.06 and consists of this page 1 and evidence pages E-1, E-2 and E-3, as well as approval document mentioned above.

The submitted documentation was reviewed by Manuel Perez, P.E.

(MIAMI-DADE COUNTY)
APPROVED

3/25/15

NOA No. 14-1224.05 Expiration Date: June 29, 2016 Approval Date: April 02, 2015 Page T

HWD Acquisition, Inc. dba Hurd Windows & Doors

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

A. DRAWINGS

- 1. Manufacturer's die drawings and sections.
- 2. Drawing No 1404, titled "Feel Safe Aluminum Clad Wood Impact Fixed Casement Window, sheets 1 through 6 of 6, dated 7/21/05, with revision E1 dated 12/18/14, prepared by W. W. Schaefer Engineering & Consulting, P.A., signed and sealed by Warren W. Schaefer, P.E.

B. TESTS

- 1. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94

along with marked-up drawings and installation diagram of an aluminum clad wood fixed window, prepared by Stork Twin City Testing Corporation, Test Report No. STCTC-180-7776.1 dated 03-04-09, signed and sealed by Tom Kolden, P.E (Submitted under NOA #09-0714.06)

- 2. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94

along with marked-up drawings and installation diagram of an aluminum clad wood fixed window, prepared by Stork Twin City Testing Corporation, Test Report No. STCTC-180-7251, dated 11/20/06, signed and sealed by Thomas Kolden, P.E. (Submitted under NOA #09-0714.06)

- 3. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94

along with marked-up drawings and installation diagram of an aluminum clad wood fixed window, prepared by Stork Twin City Testing Corporation, Test Report No. STCTC-180-7252, dated 11/20/06, signed and sealed by Thomas Kolden, P.E. (Submitted under NOA #09-0714.06)

Manuel Perez, P.E. Product Control Examiner NOA No. 14-1224.05

Expiration Date: June 29, 2016 Approval Date: April 02, 2015

HWD Acquisition, Inc. dba Hurd Windows & Doors

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

B. TESTS (CONTINUED)

- 4. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94
 - 6) Forced Entry Test, per FBC 2411 3.2.1, TAS 202-94

along with marked-up drawings and installation diagram of 6 specimens, each consisting of three-panel configuration of aluminum clad wood casement windows, prepared by Architectural Testing, Inc., Test Report No. ATI-52274.04-602-18, dated 07/07-28/04, signed and sealed by Joseph A. Reed, P.E.

(Submitted under NOA #06-013.04)

- 5. Test reports on: 1) Large Missile Impact Test per FBC, TAS 201-94
 - 2) Cyclic Wind Pressure Loading per FBC, TAS 203-94 along with marked-up drawings and installation diagram of 6 specimens each consisting of three-panel configuration of aluminum clad wood fixed windows, prepared by Architectural Testing, Inc., Test Report No. ATI-57726.01-201-44, dated 07/07-28/04, signed and sealed by Joseph A. Reed, P.E. (Submitted under NOA #06-0130.04)
- 6. Test reports on: 1) Air Infiltration Test, per FBC, TAS 202-94
 - 2) Uniform Static Air Pressure Test, Loading per FBC TAS 202-94
 - 3) Water Resistance Test, per FBC, TAS 202-94
 - 4) Large Missile Impact Test per FBC, TAS 201-94
 - 5) Cyclic Wind Pressure Loading per FBC, TAS 203-94 along with marked-up drawings and installation diagram of 6 specimens each consisting of three-panel configuration of aluminum clad fixed and casement stationary windows, prepared by Architectural Testing, Inc., Test Report No. ATI-58961.01-602-18, dated 07/28/05, signed and sealed by Joseph A. Reed, P.E.

C. CALCULATIONS:

- Anchor verification calculations and structural analysis, complying with FBC-2007 and FBC-2010, dated 05/12/11 and 10/04/11, prepared by W. W. Schaefer Engineering and Consulting, P.A., signed and sealed by Warren W. Schaefer, P.E. (Submitted under previous NOA #11-1006.06)
- 2. Glazing complies with ASTM E1300-04

(Submitted under NOA #06-0130.04)

Manuel Perez, P.E. Product Control Examiner

NOA No. 14-1224.05

Expiration Date: June 29, 2016 Approval Date: April 02, 2015

HWD Acquisition, Inc. dba Hurd Windows & Doors

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

D. OUALITY ASSURANCE

1. Miami-Dade Department of Regulatory and Economic Resources (RER).

E. MATERIAL CERTIFICATIONS

- 1. Notice of Acceptance No. 14-0423.17 issued to Eastman Chemical Company (MA) for their "Saflex Clear and Color Glass Interlayers" dated 06/19/14, expiring on 05/21/16.
- 2. Notice of Acceptance No. 13-0814.01 issued to Oldcastle Glass Inc. for their "StormGlassTM Glass Interlayer", dated 10/24/13, expiring on 12/11/18.

F. STATEMENTS

- 1. Statement letter of conformance, complying with FBC-2010 and FBC-5th Edition (2014), dated December 18, 2014, issued by W. W. Schaefer Engineering & Consulting, P.A., signed and sealed by Warren W. Schaefer, P.E.
- 2. Statement letter of no financial interest, dated December 18, 2014, issued by W. W. Schaefer Engineering & Consulting, P.A., signed and sealed by Warren W. Schaefer, P.E.

G. OTHERS

1. Notice of Acceptance No. 11-1006.06, issued to HWD Acquisition, Inc. dba Hurd Windows & Doors for their Series "Feel Safe" Aluminum Clad Wood Fixed Window – L.M.I., approved on 11/07/11 and expiring on 06/29/16.

Manuel Perez, P.E. Product Control Examiner

NOA No. 14-1224.05

Expiration Date: June 29, 2016 Approval Date: April 02, 2015

GENERAL NOTES:

- 1. THIS PRODUCT HAS BEEN TESTED, ANALYZED & APPROVED FOR DESIGN PRESSURES NOT TO EXCEED THOSE SHOWN IN THE "ALLOWABLE DESIGN PRESSURE TABLE(S)".
- 2. OPENINGS, BUCKING & BUCKING FASTENERS MUST BE PROPERLY DESIGNED & INSTALLED TO TRANSFER WIND LOADS TO THE STRUCTURE.
- 3. ALL HARDWARE & FASTENERS SHALL BE IN ACCORDANCE WITH THESE DRAWINGS & SHALL NOT VARY UNLESS SPECIFICALLY MENTIONED ON THE DRAWINGS. SPECIFIED ANCHOR EMBED TO BASE MATERIAL SHALL BE BEYOND WALL FINISH OR STUCCO.
- 4. THE DETAILS & SPECIFICATIONS SHOWN HEREIN REPRESENT THE PRODUCTS TESTED & PROPOSED FOR CONFORMANCE WITH THE FLORIDA BUILDING CODE PROTOCOLS TAS-201, 202 & 203 FOR LARGE
- 5. THIS PRODUCT HAS BEEN DESIGNED IN ACCORDANCE WITH AND MEETS THE REQUIREMENTS OF THE FLORIDA BUILDING CODE (FBC) INCLUDING HIGH VELOCITY HURRICANE ZONES (HVHZ).

 6. IMPACT SHUTTERS ARE NOT REQUIRED WITH THIS PRODUCT.
- 7. ALL ANCHORS SECURING PRODUCT FRAMES TO PRESSURE TREATED BUCKS OR WOOD FRAMING SHALL BE CAPABLE OF RESISTING CORROSION CAUSED BY THE PRESSURE TREATING CHEMICALS IN
- 8. DETERMINE THE POSITIVE & NEGATIVE DESIGN LOADS TO USE WHEN REFERENCING THESE DOCUMENTS IN ACCORDANCE WITH THE GOVERNING CODE AND GOVERNING WIND VELOCITY. FOR WIND LOAD CALCULATIONS IN ACCORDANCE WITH THE FLORIDA BUILDING CODE, A DIRECTIONALITY FACTOR OF Kd = 0.85 May be applied per the asce-7 standard.
- 9. NO INCREASE IN ALLOWABLE STRESS HAS BEEN USED IN THE CERTIFICATION OF THIS PRODUCT. WIND LOAD DURATION FACTOR Cd = 1.6 WAS USED FOR WOOD SCREW ANALYSIS ONLY.

 10. MATERIALS, INCLUDING BUT NOT LIMITED TO STEEL SCREWS, THAT COME INTO CONTACT WITH OTHER DISSIMILAR MATERIALS SHALL MEET THE REQUIREMENTS OF FLORIDA BUILDING CODE.
- 11. All wood members of this product that may possibly come into contact with masonry OR CONCRETE SUBSTRATES, ARE SUBJECT TO MOISTURE &/OR ARE SUBJECT TO THE OUTSIDE ENVIRONMENT SHALL BE OF AN APPROVED DURABLE SPECIES OR BE TREATED IN AN APPROVED METHOD WITH AN APPROVED PRESERVATIVE PER FBC REQUIREMENTS.

CORNER CONSTRUCTION:

WOOD FRAME: SQUARE CUT, RABBETED, SILICONE SEALED & SECURED WITH THREE (3) 16 GA. X 1/2* X 2" CROWN STAPLES.


FRAME CLAD: MITER CUT, JOINED WITH A CORNER KEY & TWO (2) NO. 7 X 1/2" SCREWS & SEALED WITH A FOAM GASKET.

WOOD SASH; MORTISE & TENON CONSTRUCTION AND SECURED WITH TWO (2) 14 GA. X 2 1/2" T-NAILS, SASH CLAD: SQUARE CUT, BUTTED TOGETHER AND SNAP FIT TO SASH AND SEALED WITH SELECONE.

FRAME ANCHOR REQUIREMENTS TABLE						
OPENING TYPE (SUBSTRATE)	FRAME/FIN TO OPENING FASTENER TYPE	MINIMUM EMBED	MINIMUM EDGE DIST.			
FRAME SCREWS						
MIN. 2X4 WOOD FRAME OR BUCK (MIN. GR. 3 & G=0.55)	NO. 10 SMS OR WOOD SCREW	1 1/4"	3/4"			
MIN. 18 GA. 33 KSI METAL STUD	NO. 10 GR. 5 SELF TAP/DRILL SCREW	FULL	1/2"			
MIN. 1/8" THK A36 STEEL	NO. 10 GR. 5 SELF TAP/DRILL SCREW	FULL	1/2"			
MIN. 1/8" THK 6063-T5 ALUM.	NO. 10 GR. 5 SELF TAP/DRILL SCREW	FULL	1/2"			
C-90 CMU/2500 PSI CONCRETE	(1) 1/4" CONCRETE SCREW	1 1/4"	2"			
(2) NAILING FIN FASTENERS						
MIN. 2X4 WOOD FRAME OR BUCK (MIN. GR. 3 & G=0.55)	NO. 8 SMS SCREW	1 1/8"	1/2"			
MIN. 2X4 WOOD FRAME OR BUCK (MIN. GR. 3 & G=0.55)	11 GA. ROOFING NAIL	1 3/4"	1/2"			
MIN. 1/8" THK A36 STEEL	NO. 8 GR. 5 SELF TAP/DRILL SCREW	FULL	1/2"			
MIN. 1/8" THK 6063-T5 ALUM.	NO. 8 GR. 5 SELF TAP/DRILL SCREW	FULL	1/2"			

(1) CONCRETE SCREWS SHALL BE ELCO ULTRACONS (C.S.), ELCO CRETE-FLEX (S.S.), ITW RAMSET/RED HEAD TAPCONS (C.S. OR S.S.) OR HILTI KWIK-CON II (C.S OR S.S.).

(2) NAIL FIŃ SCREWS SHALL BE À PAN HEAD ÓR HEX HEAD SCREW OR`HAVE A FLAŤ WASHER AT THE SCREW HEAD.



ALLOWABLE DESIGN PRESSURE

SEE SINGLE WINDOW SIZE/PRESSURE TABLE ON SHEET 2

PRODUCT REVISED as complying with the Florida Building Code Acceptance No 14-1224.05 Expiration Date June 24, 2016 By Mull Control
Miami Dade Product Control

W. SCHAEFER
W. SCHAEFER
CONSULTING, F
7480 150TH COUF
PALM BEACH CARDEN
PHONE: 561-74 1 8 2014 DEC 1404

SHEET NO.

OF

W.W.S.

7/21/05

HWD ACQUISTTON, INC. dba HURD WINDOWS & DOORS 575 S. WHELEN AVE. MEDFORD, WI 54451 800-433-4873

R. ENGINEERING
P.A. (CA 6809)
WATE NORTH
ENS. 1 33418

OT: 1=16

WINDOW

CASEMENT

FIXED

IMPACT

WOOD


CLAD

ALUMINUM

ALLOWABLE SINGLE WINDOW SIZE/DESIGN PRESSURE									
MAXIMUM									
FRAME	FRAME	ALLOWABLE PRESSURE (PSF) GLASS GLASS GLASS GLASS							
LONG	SHORT						ISS		ASS
DIMENSION	1		ION	OPTION		OPTION		OPTIONS	
1	DIMENSION	1 2		3		4 & 5			
(IN.)	(IN.)	POS	NEG	POS	NEG	POS	NEG	POS	NEG
	45	\sim	\sim	><	><	65.0	80.0	\sim	> <
144	29	><	> <	65.0	70.0	65.0	80.0	65.0	70.0
	18	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
	50	> <	> <	> <	> <	65.0	80.0	><	> <
132	32	>	$\supset \subset$	65.0	70.0	65.0	80.0	65.0	70.0
152	22	> <	> <	65.0	85.0	65.0	80.0	65.0	70.0
	18	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
	55	\sim	> <	\sim		65.0	80.0		>
100	36	\sim	\sim	65.0	70.0	65.0	80.0	65.0	70.0
120	24	\supset	\sim	65.0	85.0	65.0	80.0	65.0	70.0
	21	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
	61					65.0	80.0	\sim	\sim
108	40	>		65.0	70.0	65.0	80.0	65.0	70.0
·	24	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
	65	55.5	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	\ <u>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</u>	65.0	80.0	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	42	>	>	65.0	70.0	65.0	80.0	65.0	70.0
101	28	\Longrightarrow	\Leftrightarrow	65.0	85.0	65.0	80.0	65.0	70.0
	24	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
	65	05.0	70.0	05.0	65.0			03.0	70.0
	-	\bowtie	\Longrightarrow	CE O	70.0	65.0	80.0	()	70.0
96	44	\bowtie	\Leftrightarrow	65.0	1	65.0	80.0	65.0	
	30	65.0	70.0	65.0 65.0	85.0 85.0	65.0 65.0	80.0 80.0	65.0 65.0	70.0 70.0
-	27 65	100.0	10.0	 	\```	65.0	80.0	K	/0.0
	48	\Longrightarrow	\Longrightarrow	65.0	70.0	65.0	80.0	65.0	70.0
90	32	\Longrightarrow	\Longrightarrow	65.0	85.0	65.0	80.0	65.0	70.0
	29	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
 	65	05.0	70.0	03.0	35.0	65.0	80.0	03.0	70.0
	51	\Longrightarrow	\Longrightarrow	65.0	70.0	65.0	80.0	65.0	70.0
84		\bowtie	\Longrightarrow	65.0		1		-	
64	34	650	700	$\overline{}$	85.0	65.0	80.0	65.0	70.0
 	31	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
	65	\Leftrightarrow	\Longrightarrow	(F)	1700	65.0	80.0	(F)	70.0
78	55	\Longrightarrow	\Leftrightarrow	65.0	70.0	65.0	80.0	65.0	70.0
	37		200	65.0	85.0	65.0	80.0	65.0	70.0
 	33	65.0	70.0	65.0	85.0	65.0	80,0	65.0	70.0
	65	$\stackrel{\textstyle{\scriptstyle{(}}}{\longleftrightarrow}$	\iff			65.0	80.0		
72	60	\triangleright	\sim	65.0	70.0	65.0	80.0	65.0	70.0
	40	\geq	\geq	65.0	85.0	65.0	80.0	65.0	70.0
ļ	36	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
64	65	\bowtie	\bowtie	65.0	70.0	65.0	80.0	65.0	70.0
	45	$\geq \leq$	\geq	65.0	85.0	65.0	80,0	65.0	70.0
	40	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
60	60	$\geq \leq$	$\geq \leq$	65.0	70.0	65.0	80.0	65.0	70.0
	48	$\geq \leq$	$\geq \leq$	65.0	70.0	65.0	80.0	65.0	70.0
	43	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
52	52	$\geq \leq$	$\geq \leq$	65.0	85.0	65.0	80.0	65.0	70.0
J2	50	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
48	48	65.0	70.0	65.0	85.0	65.0	80.0	65.0	70.0
NOTES:									

NOTES:

- 1. SEE GLAZING DETAILS FOR GLAZING OPTIONS
 2. CROSSED OUT BOXES DESIGNATE SIZES NOT ACCEPTABLE FOR THE RESPECTIVE GLASS OPTION.
- 3. ALL DIMENSIONS ARE +/-3/16



25 GA. X 2 3/8" X 10 1/4" GALVANIZED MULLION END REINFORCEMENT PLATE STAPLED TO EACH JAMB WITH TEN(10) 16 GA. X 7/16" X 9/16" LONG STAPLES. (TYP. EACH END OF EACH MULLION)

NO. 10 SCREWS PER FRAME ANCHOR REQUIREMENTS TABLE. FOUR (4) TOTAL PER MULLION END WHETHER WINDOW IS SCREW MOUNTED OR FIN MOUNTED.

MULTIPLE UNIT NOTES:

- 1. THE MAXIMUM ALLOWABLE PRESSURE FOR A COMBINED UNIT IS RESTRICTED BY THE LESSER OF THE INDIVIDUAL WINDOW ALLOWABLE PRESSURE OR THE ALLOWABLE MULLION PRESSURE. SEE MULLION LOAD TABLE ON THIS SHEET FOR ALLOWABLE UNIT PRESSURE.
- 2. WINDOWS MAY BE STACKED HORIZONTAL OR VERTICAL. TO INSURE THAT THE DEAD WEIGHT OF THE ABOVE WINDOW(S) WILL NOT CAUSE UNDO STRESS ON THE BELOW WINDOW, WHEN VERTICALLY STACKED, THE MANUFACTURER/INSTALLER SHALL LIMIT THE SAG OF THE HORIZONTAL MULLION TO MAX. 1/8".

EXTERIOR ELEVATION: MULTIPLE SIDE-BY-SIDE FIXED WINDOWS

SCALE: 3/4"=1'-0"

(FOR INDIVIDUAL WINDOW INSTALLATION & DETAILS, SEE SINGLE WINDOW ELEVATIONS) (DOUBLE WINDOW SHOWN. MORE THAN 2 WINDOWS MAY BE MULLED TOGETHER IN ONE DIRECTION INTO ONE OPENING.) NOTE: MULLION MAY BE HORIZONTAL OR VERTICAL


ALLOWABLE PRESSURE (SIDE-BY-SIDE UNITS)

(CIDE DI CIDE CITIC)							
MAXIMUM MULLION SPAN	Maximum Load Width	ALLOWABLE PRESSURE (P.S.F.)					
(IN.)	(IN.)	POSITIVE	NEGATIVE				
72	60	61.8	66.5				
72	54	65.0	70.0				
66	66	65.0	70.0				
60	72	65.0	70.0				
60	48	65.0	85.0				

LESSER OF THE PRESSURE SHOWN IN THIS TABLE & THAT ALLOWED FOR THE INDIVIDUAL WINDOW SHALL CONTROL AS ALLOWABLE FOR THE OVERALL UNIT. LOAD WIDTH VALUES ARE +/- 1/2"

PRODUCT REVISED as complying with the Florida Building Code
Acceptance No 14-1224 05
Expiration Date 1 1106 79/2016

Miami Dade Product Control



W. SCHAEFER CONSULTING, P 18 2014 DEC

CASEMENT WINDOW

FIXED

WOOD IMPACT

ATE: 7/21/<u>05</u>

1404 SHEET NO. 2 of

